

HEAR. CONNECT. GET IT DONE.

BUILT FOR THE JOB. DESIGNED TO PERFORM.



HS2

Clip In Hard Hat Headset

Dual Muff Headset W/Push-To-Talk

The HS2 is designed for optimal protection and clear communication. Equipped with a high-quality noise-canceling microphone and foam earphone padding for enhanced comfort, this headset easily clips onto any hard hat. It includes a PTT button on the earcup and a lightweight, flexible boom mic to ensure reliable performance in various environments.

HS2-CAB

HS-PTTCAB

COMFORTABLE FIT

This is one of the most comfortable headsets designed for users who need to stay mobile and productive throughout the day. Its lightweight, ergonomic design delivers a secure yet comfortable fit, allowing you to move freely without feeling weighed down or restricted. Whether you're working long shifts, coordinating in fast-paced environments, or constantly on the move, this headset delivers.



HEAVY-DUTY
360° ROTATING CLIP



DETACHABLE
COIL DESIGN



DURABLE CONSTRUCTION
FOR LONG-LASTING USE



COMPATIBLE WITH
ALL RADIO MODELS

HS2

CLIP IN HARD HAT HEADSET

Dual Muff Headset
W/Push-To-Talk



FEATURES

*Hardhat not included

- Clips directly onto Hard Hat
- Extremely comfortable and stable
- PTT button on earcup
- High-quality and loud speakers with foam pad ear cushions to block out external sound and seal in receive audio
- Noise-canceling microphone on adjustable boom with foam windsock to reduce wind noise
- Compatible with 5-pin Headset Cables with or without inline PTT in an extensive variety of device connectors (Cables sold separately)

PRODUCT SPECIFICATIONS

DIMENSIONS

Earcup Width	~3.2 in. (82mm)
Earcup Height	~4.3 in. (110mm)
Mic Boom Length	~5.1 in. (130mm)
Overall Weight (not including cable)	~17.6 oz (500g)

AUDIO

Speaker Sensitivity	99 dB SPL
Speaker Power	1 W (nominal), 1.2 W (max)
Speaker Impedance	16 Ohms $\pm$ 15%
Microphone Sensitivity	-44 dBV
Microphone Frequency Response	50 Hz to 10 kHz
Microphone Directionality	Uni-Directional Noise Canceling
Device Connector	5-pin Headset Connector
Operating Temperature	-4°F to 122°F (-20°C to 50°C)

PRODUCT OPTIONS

HS2-CAB

Detachable Coil Cable is the ideal replacement or spare cable. Built for durability and reliability, this cable ensures seamless compatibility with multiple radio models. Its coiled design offers flexibility and reduced tangling, making it perfect for demanding environments.



OR

HS-PTTCAB

Detachable Coil Cable with Inline PTT and Removable Rings is the ideal replacement or backup cable. Featuring a newly designed inline PTT button with two removable PTT rings. Its heavy-duty rotating clip ensures secure attachment.

